



Dimensiones (mm)

	$b_1 \pm 1,50$	$A \pm 0,10$ $B \pm 0,75$ h_1	$h \pm 0,08$	l	$+3$ -0 k_1	$+0,10$ -0 k_2	$+0,10$ -0 n	$+3$ -0 c	$g \pm 0,75$	$f \pm 0,75$	$p \pm 0,75$	r_s	m_1 $+0,06$ -0	m_2 $+0$ $-0,06$	$u_1 \pm 0,10$	$u_2 \pm 0,10$	$f/5m$ max. mm	f/m max. mm
T70/A	70	65	·	·	9	·	34	6	6	8	·	1,5	3	2,97	3,5	3	2,5	0,5

Distanc between holes, fishplates and bolts (mm)

	d	d_1	b_2	$b_3 \pm 0,20$	l_1 $+3$ -0	$l_2 \pm 0,20$	$l_3 \pm 0,20$	v $+3$ -0	Bolt	Washer
T70/A	13	26	70	42	250	105	25	10	M12x35	A-12

Technical characteristics

	Section cm 2	Weight kg/m	e cm	I_{xx} cm 4	W_{xx} cm 3	i_{xx} cm	I_{yy} cm 4	W_{yy} cm 3	i_{yy} cm
T70/A	9,4	7,379	2,034	40,95	9,169	2,087	18,86	5,389	1,417

