



### Dimensiones (mm)

	$b_1 \pm 1,50$	$h_1 \pm 0,75$	$h \pm 0,05$	$l$	$^{+3}_{-0}$ $k_1$	$^{+0,05}_{-0}$ $n$	$^{+3}_{-0}$ $c$	$g \pm 0,75$	$f \pm 0,75$	$r_s$	$^{+0,03}_{-0}$ $m_1$	$^{+0}_{-0,03}$ $m_2$	$u_1 \pm 0,10$	$u_2 \pm 0,10$	Enderezado / Straightness	
															f/5m max. mm	f/m max. mm
<b>T89/B</b>	89	62	61	156	16	34	10	8	11	3	6,4	6,37	7,14	6,35	1,25	0,25

### Distanc between holes, fishplates and bolts (mm)

	$d$	$d_1$	$b_2$	$b_3 \pm 0,20$	$l_1$ $^{+3}_{-0}$	$l_2 \pm 0,20$	$l_3 \pm 0,20$	$v$ $^{+3}_{-0}$	Bolt	Washer
<b>T89/B</b>	13	26	90	57,2	305	114,3	38,1	28	M12x60	A-12

### Technical characteristics

	Section cm 2	Weight kg/m	$e$ cm	$I_{xx}$ cm 4	$W_{xx}$ cm 3	$i_{xx}$ cm	$I_{yy}$ cm 4	$W_{yy}$ cm 3	$i_{yy}$ cm
<b>T89/B</b>	15,77	12,38	2,032	59,83	14,35	1,948	52,41	11,78	1,823

